

WAFER-SPHERE® BUTTERFLY VALVES FOR VACUUM SERVICE

For vacuum applications, WAFER-SPHERE high-performance butterfly valves offer not only the conventional butterfly valve advantages of compactness, minimum amount of surface area exposed to the vacuum, and simplicity of design, but also the tight shut-off and long cycle life resulting from the WAFER-SPHERE valves unique construction.

Standard WAFER-SPHERE valves are rated for vacuum services down to 2×10^{-2} Torr, with a specially prepared high vacuum valve available for lower applications, as indicated in Table 1.

FEATURES

Positive Shut-off

- JAMESBURY® flexible lip seat design provides positive shut-off throughout the full pressure/vacuum rating range of the valve while minimizing out-gassing problems characteristic of resilient materials. High vacuum valves are guaranteed to have a leakage rate not to exceed 1×10^{-5} std. cc/sec. of helium.

High Cycle Life

- An offset shaft and disc arrangement causes the disc to lift away from the seat to provide for extremely long cycle life while enhancing sealing ability.

Two versions available

- Standard WAFER-SPHERE valves are offered for vacuums to 2×10^{-2} Torr for services below that, a high vacuum valve is available, specially cleaned, tagged and sealed in polyethylene bags.

Special testing and certification available

- High vacuum valves can be tested on a helium mass spectrometer with a maximum sensitivity of 2×10^{-10} std. cc/sec., and certified to have a leakage rate not to exceed 1×10^{-5} std. cc/sec. of helium.

VACUUM AND RECOMMENDED TEMPERATURE RATINGS

TABLE 1 WAFER-SPHERE Butterfly Valves		
Type of Valve	XTREME® Seat & Carbon Filled Enhanced PTFE Seal	Vacuum Rating
Standard valves* All sizes and styles	-50°F to +500°F (-45°C to +260°C)	2×10^{-2} Torr
High Vacuum valves All sizes and styles	+20°F to +300°F (-6.67°C to +126.67°C)	Below 2×10^{-2} Torr

*NOTE: Standard valves with PTFE seat & seal are rated to -50°F to +400°F (-45°C to +204°C)

PRESSURE CONVERSION TABLE

	POUNDS PER SQUARE INCH (psi)		KILOGRAMS PER SQUARE CENTIMETER (kg/cm)		INCHES OF WATER COLUMN (in. w.c.)		INCHES OF MERCURY (in. hg.)		MILLIMETER OF MERCURY (mm. hg.)		MICRONS (Torr x 1000)	VALVE APPLICATIONS		
	GAGE	ABSOLUTE	GAGE	ABSOLUTE	GAGE	ABSOLUTE	GAGE	ABSOLUTE	GAGE	ABSOLUTE (Torr)				
↑ PRESSURE ↓	3	18		1.266	100	500	6	36	100	900	760,000	↑ USE STANDARD VALVES ↓		
	2	16	0.141	1.125	50	450	3	33		800				
ATMOSPHERE	0	14.7	0	1.033	0	406.8	0	29.92	0	760				
↑ VACUUM ↓		14		0.984						700				
	2	12	0.141	0.844	50	350	3	27	100	600				
	3	10	0.281	0.703	100	300	6	24	200	500				
	4						9	21		500				
		14.6996	.0004 or 4×10^{-4}	1.03297	.00003 or 3×10^{-5}	406.79	.01 or 1×10^{-2}	29.91	.0008 or 8×10^{-4}	759.98			.02 or 2×10^{-2}	20
		2×10^{-7}		1.36×10^{-2}		5×10^{-6}		4×10^{-7}		1×10^{-5}			.01 or 1×10^{-2}	
	14.7	0	1.033	0	406.8	0	29.92	0	760	0			0	

HOW TO ORDER WAFER-SPHERE BUTTERFLY VALVES FOR VACUUM SERVICE

High vacuum type 815 and 830 WAFER-SPHERE valves have the letters "HV" succeeding the body designation, i.e., Figure 815LHV-11-2236X2. Certified high vacuum valves use the letters "HVC."

For complete ordering information on WAFER-SPHERE high-performance butterfly valves refer to Bulletin W101-6.

Subject to change without prior notice.

Metso Automation Inc.

Europe, Levytie 6, P.O. Box 310, 00811 Helsinki, Finland.
Tel. +358 20 483 150. Fax +358 20 483 151

North America, 44 Bowditch Drive, P.O. Box 8044, Shrewsbury, MA 01545, USA.
Tel. +1 508 852 0200. Fax +1 508 852 8172

Europe, 6-8 rue du Maine, 68271 Wittenheim Cedex, France.
Tel. +33 (0)3 89 50 64 00. Fax +33 (0)3 89 50 64 40

South America, Av. Independência, 2500- Iporanga, 18087-101, Sorocaba-São Paulo Brazil. Tel. +55 15 2102 9700. Fax +55 15 2102 9748/49

Asia Pacific, 238A Thomson Road, #25-09 Novena Square Tower A, 307684 Singapore.
Tel. +65 6511 1011. Fax +65 6250 0830

China, 19/F, the Exchange Beijing, No. 118, Jianguo Lu Yi, Chaoyang Dist, 100022 Beijing, China.
Tel. +86-10-6566-6600. Fax +86-10-6566-2575

Middle East, Roundabout 8, Unit AB-07, P.O. Box 17175, Jebel Ali Freezone, Dubai, United Arab Emirates. Tel. +971 4 883 6974. Fax +971 4 883 6836

www.metso.com/automation

